

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-35°C TO +85°C (NOTES 1)	STORAGE TEMPERATURE RANGE	-10°C TO +60°C
	VOLTAGE	30V AC	APPLICABLE CONNECTOR	BM10*(0.8)-*DP-0.4V (**)
	CURRENT	0.3A		

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

GENERAL EXAMINATION	CONFIRMED VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

ELECTRIC CHARACTERISTICS

CONTACT RESISTANCE	20mV AC OR LESS 1kHz, 1mA.	100mΩ MAX.	X	—
INSULATION RESISTANCE	100V DC.	50MΩ MIN.	X	—
VOLTAGE PROOF	100V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	—

MECHANICAL CHARACTERISTICS

INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>PIN COUNTS</th> <th>INSERTION FORCE (N MAX)</th> <th>WITHDRAWAL FORCE (N MIN)</th> </tr> </thead> <tbody> <tr><td>BM10*(0.8)-*DS/DP-0.4V</td><td></td><td></td></tr> <tr><td>10</td><td>15.4</td><td>2.6</td></tr> <tr><td>16</td><td>20.7</td><td>3.6</td></tr> <tr><td>20</td><td>24.3</td><td>4.4</td></tr> <tr><td>24</td><td>27.8</td><td>5.1</td></tr> <tr><td>30</td><td>33.1</td><td>6.2</td></tr> <tr><td>34</td><td>36.6</td><td>6.9</td></tr> <tr><td>40</td><td>41.9</td><td>8.0</td></tr> <tr><td>50</td><td>50.7</td><td>9.8</td></tr> <tr><td>60</td><td>59.5</td><td>11.7</td></tr> </tbody> </table>	PIN COUNTS	INSERTION FORCE (N MAX)	WITHDRAWAL FORCE (N MIN)	BM10*(0.8)-*DS/DP-0.4V			10	15.4	2.6	16	20.7	3.6	20	24.3	4.4	24	27.8	5.1	30	33.1	6.2	34	36.6	6.9	40	41.9	8.0	50	50.7	9.8	60	59.5	11.7	X	—
	PIN COUNTS	INSERTION FORCE (N MAX)	WITHDRAWAL FORCE (N MIN)																																		
BM10*(0.8)-*DS/DP-0.4V																																					
10	15.4	2.6																																			
16	20.7	3.6																																			
20	24.3	4.4																																			
24	27.8	5.1																																			
30	33.1	6.2																																			
34	36.6	6.9																																			
40	41.9	8.0																																			
50	50.7	9.8																																			
60	59.5	11.7																																			
MECHANICAL OPERATION	10TIMES INSERTIONS AND WITHDRAWAL.	① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—																																	
VIBRATION	FREQUENCY 10 TO 55 TO 10 Hz, APPROX 5min, SINGLE AMPLITUDE 0.75 mm, 10CYCLES, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—																																	
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—																																	

ENVIRONMENTAL CHARACTERISTICS

RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → +85 °C TIME 30 → 30 min UNDER 5 CYCLES. (RELOCATION TIME TO CHAMBER: WITHIN 2 ~3 MIN)	① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 50MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.	① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 25MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—
SULPHUR DIOXIDE	EXPOSED IN 25 PPM FOR 96h, 25°C, 75%. (REFER TO JIS C 60068)	① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
1	DIS-H-003833	NY. YAMASHIRO	TS. MIYAZAKI	09. 04. 15

REMARKS NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT Unless otherwise specified, refer to JIS C 5402 and IEC 60512	APPROVED	KH. IKEDA	08. 04. 22
	CHECKED	KY. MIDORIKAWA	08. 04. 22
	DESIGNED	TH. ARAI	08. 04. 22
	DRAWN	SH. HOSODA	08. 04. 21

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. **ELC4-318423-01**

HRS	SPECIFICATION SHEET	PART NO.	BM10NB (0.8)-*DS-0.4V (51)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL684-****-*-51	1/1